



NOTES:

ELECTRICAL:

1. VOLTAGE RATING: 125 VAC RMS
2. CURRENT RATING: 1.5AMP
3. CONTACT RESISTANCE: 100MILLIOHMS MAX
4. INSULATION RESISTANCE: 100 MEGOHMS MIN @500 VDC
5. DIELECTRIC STRENGTH: 750 VAC RMS 60Hz, 1MIN

ENVIRONMENTAL:

1. STORAGE: -40°TO+85°
2. OPERATION: 0°TO70°

MECHANICAL:

1. HOUSING MATERIAL: PC
2. INSERT MATERIAL: FAME RETARDANCY ABS
3. PCB MATERIAL: FR-4 T=1.6mm
4. CONTACT MATERIAL: PHOSPHOR BRONZE
STAMP PIN T=0.30mm
5. RJ45 JACK ;LIFE: 750 TIMES MIN

③	LABLE	1 PCS	“ CAT 6A Inline Coupler”
②	shell	1 PCS	ABS shell
①	CONNECTER	2PCS	RJ45 Female (8P8C) gold plated
NO.	PARTS NAME	Q'TY	SPECIFICATION

APPROVED	CHECKED	DRAWN	CUSTOMER	
			ITEM NO.	685-U
			DRAW NO.	
			UNIT	mm
			SCALE	NONE

Description:

Cat 6A Inline Coupler UTP

